



X-Trim Candlewick

The X-Trim line of wick was developed for use in pillars. It also can improve the performance of scented container candles. Our balanced construction is designed to produce a gentle curl that is self-trimming and will not over curl. The X-Trim wick provides a straight wick posture and curls high on the wick's stalk. This raises the flame and helps maintain a centered pool. Fil-Tec's scientifically engineered chemical treatment reduces afterglow, enhances the self-trimming and helps control the curl. The wick's open construction allows for better capillary flow when using heavily scented paraffin, vegetable based and beeswax wax blends. Our Patented construction also delivers a consistent consumption rate. Fil-Tec X-Trim wick offers a higher yield than conventional braided wick, which means lower material costs and longer production runs.

WICK & PART NUMBER	FLAME HEIGHT	RATE OF CONSUMPTION	POOL DIAMETER	WICK YIELD
X-Trim FT 1.223 Part # 54376	.63 inch 1.6 cm	2.3 grams / hour	1.223 inch 3.1 cm	2387 yards / lb. 4812 meters / kg.
X-Trim FT 1.305 Part # 54480	.76 inch 1.9 cm	2.7 grams / hour	1.305 inch 3.3 cm	1814 yards / lb. 3657 meters / kg.
X-Trim FT 1.446 Part # 54377	.85 inch 2.2 cm	3.1 grams / hour	1.446 inch 3.7 cm	1649 yards / lb. 3324 meters / kg.
X-Trim FT 1.572 Part # 54422	1.0 inch 2.5 cm	3.9 grams / hour	1.572 inch 4.0 cm	1277 yards / lb. 2574 meters / kg.
X-Trim FT 1.954 Part # 54260	1.4 inch 3.6 cm	5.2 grams / hour	1.954 inch 5.0 cm	1120 yards / lb. 2258 meters / kg.
X-Trim FT 2.009 Part # 54178	1.5 inch 3.8 cm	5.6 grams / hour	2.009 inch 5.1 cm	880 yards / lb. 1774 meters / kg.
X-Trim FT 2.115 Part # 54474	1.5 inch 3.8 cm	5.6 grams / hour	2.115 inch 5.4 cm	692 yards / lb. 1395 meters / kg.
X-Trim FT 2.162 Part # 54160	1.5 inch 3.8 cm	5.9 grams / hour	2.162 inch 5.5 cm	722 yards / lb. 1455 meters / kg.
X-Trim FT 2.236 Part # 54177	1.7 inch 4.3 cm	6.2 grams / hour	2.236 inch 5.7 cm	570 yards / lb. 1149 meters / kg.
X-Trim FT 2.305 Part # 54308	1.5 inch 3.8 cm	5.8 grams / hour	2.305 inch 5.9 cm	484 yards / lb. 976 meters / kg.
X-Trim FT 2.370 Part # 54321	1.8 inch 4.6 cm	7.0 grams / hour	2.370 inch 6.0 cm	388 yards / lb. 782 meters / kg.
X-Trim FT 2.506 Part # 54320	2.0 inch 5.1 cm	7.0 grams / hour	2.506 inch 6.4 cm	442 yards / lb. 891 meters / kg.

Our product description is very "user-friendly". The description represents the 2 hour pool diameter in a 140° melt point straight cut paraffin wax. This method allows the user to easily compare wick size and performance. This chart provides the candle maker a starting point for wick selection. Your wick selection will depend on wax blend, color and scent additives.

12/5/2008

FIL-TEC Inc. P.O. Box B Hagerstown, Maryland 21741-1191 USA

Phone: 301-824-6166 Fax: 301-824-1125