



Zinc Core Candlewick

For those manufacturers that use a zinc core we offer a full line of sizes with our knitted construction that works well in all wax blends. With our zinc core you'll enjoy a consistent burning wick with a money-saving yield advantage.

WICK & PART NUMBER	FLAME HEIGHT	RATE OF CONSUMPTION	POOL DIAMETER	WICK YIELD
Zinc Core FT 1.600 Part # 54619	.81 inch 2.1 cm	3.1 grams / hour	1.600 inch 4.1 cm	448 yards / lb. 903 meters / kg.
Zinc Core FT 1.705 Part # 54615	1.3 inch 3.3 cm	3.4 grams / hour	1.705 inch 4.3 cm	436 yards / lb. 879 meters / kg.
Zinc Core FT 1.832 Part # 54549	1.4 inch 3.6 cm	4.3 grams / hour	1.832 inch 4.7 cm	396 yards / lb. 798 meters / kg.
Zinc Core FT 2.082 Part # 54003	1.1 inch 2.8 cm	5.1 grams / hour	2.082 inch 5.3 cm	391 yards / lb. 788 meters / kg.
Zinc Core FT 2.185 Part # 54004	1.6 inch 4.1 cm	6.2 grams / hour	2.185 inch 5.6 cm	331 yards / lb. 667 meters / kg.
Zinc Core FT 2.231 Part # 54005	1.6 inch 4.1 cm	6.3 grams / hour	2.231 inch 5.7 cm	315 yards / lb. 635 meters / kg.
Zinc Core FT 2.449 Part # 54006	1.75 inch 4.5 cm	7.3 grams / hour	2.449 inch 6.2 cm	257 yards / lb. 518 meters / kg.
Zinc Core FT 2.700 Part # 54407	1.8 inch 4.6 cm	7.8 grams / hour	2.700 inch 6.9 cm	190 yards / lb. 383 meters / kg.

Our product description is very "user-friendly". The description represents the 2 hour pool diameter in a 140° melt point straight cut paraffin wax. This method allows the user to easily compare wick size and performance. This chart provides the candle maker a starting point for wick selection. Your wick selection will depend on wax blend, color and scent additives.

3/11/2009